



FLAME RETARDANT



NO CURLING

APPLICATIONS

- > **ONE SIDE PRINTING**
- > **DIGITAL PRINTING:** solvent / eco-solvent / UV and Latex inks
- > **INDOOR COMMUNICATION:** displays / roll-up / signage / POS / hanging banners / window dressing
- > **ECOLOGICAL PRODUCT:** EverGreen collection / PVC free / Phtalates free / Formaldehydes free / Phosphates free / Glycol ether free

PRODUCT PACKAGING

- > **SUPER WIDE FORMAT:** 3.20 m
Rolls of: 60 ml - printable side outside
- > **WIDE FORMAT:** 0.90m / 1.06m / 1.37m / 1.62m
Rolls of: 50 ml - printable side outside

PRODUCT CHARACTERISTICS

WEIGHT	280 g/m ²		
COATING	EverGreen coating	Base cloth	Polyester
COLOUR	White 9263	Finish	Inkjet lacquer One side
THICKNESS	0.33 mm	Translucency XP T 54 199	16 %
TENSILE STRENGTH NF EN ISO 1421	150 / 150 daN	Tear strength DIN 53363	20 / 20 daN
FIRE RETARDANT	M1 / B1 B-s1-d0 (EN 13 501-1) NFPA 701 / ASTM E 84		



DICKSON COATINGS

Company with management system certified by DNV-GL
ISO 9001 • ISO 14001

www.dickson-coatings.com
www.evergreen-fabrics.com

EDITION 01/2016
Average values +/- 10 %